

IECEX 63A DISTRIBUTION BOARD

ORDER CODE: 63DB

DESCRIPTION

Our portable 63A 3-phase power distribution boards offer a simple and reliable electrical distribution panel for use in hazardous areas. Constructed from IECEx certified equipment, heavy-duty industrial frames and castors, the units are suitable for use in zone 1 and 2 hazardous areas and harsh environments. Improve power accessibility by providing a simple portable panel with multiple outlets.

KEY FEATURES

- ATEX and IECEx certified for zone 1 and 2
- Simple plug-in operation
- Self-contained distribution panel
- Portable design with castors
- Robust frame
- Multiple protected outlets
- Waterproof & dustproof
- AS/NZS 60079 compliant



TECHNICAL SPECIFICATION

Zone Rating	Zone 1 & 2
Temperature Classification	T6
Input	1x 63A 3-phase
Input Voltage	380-480V
Outputs	1x 63A 3-phase, 1x 32A 3-phase, 4x 16A 1-phase *
Output Voltages	380-480V / 200-250V
Frequency	50/60Hz
Pin Arrangement	3P+N+E / 1P+N+E
Ingress Protection	IP66
Plug Options	CEAG, STAHL **
Socket Options	CEAG, STAHL **

* Other output options available.

** Other plug and socket options available upon request.

IECEX 125A DISTRIBUTION BOARD

ORDER CODE: 125DB



DESCRIPTION

Our portable 125A 3-phase power distribution boards offer a simple and reliable electrical distribution panel for use in hazardous areas. Constructed from IECEX certified equipment and heavy-duty industrial frames, the units are suitable for use in zone 1 and 2 hazardous areas and harsh environments. Improve power accessibility by providing a simple portable panel with multiple outlets.

KEY FEATURES

- IECEX and ATEX certified for zone 1 and 2
- Simple plug-in operation
- 30m power supply cable
- Self-contained distribution panel
- Portable design
- Robust lifting frame (AS4991)
- Emergency stop button
- Multiple RCBO protected outlets
- Waterproof & dustproof
- AS/NZS 60079 compliant

TECHNICAL SPECIFICATION

Zone Rating	Zone 1 & 2
Temperature Classification	T4
Gas Group	IIB+H2
Ambient Temperature	-20°C to +55°C
Input	125A 3-phase
Input Voltage	400VAC (nominal)
Outputs	1x 63A 3-phase, 2x 32A 3-phase, 4x 16A 1-phase
Output Voltages	400VAC / 230VAC (nominal)
Frequency	50/60Hz
Pin Arrangement	3P+N+E / 1P+N+E
Ingress Protection	IP66
Plug & Socket type	CEAG
Input Cable Length	30 metres