

## IECEX 32A EXTENSION LEAD

ORDER CODE: 32EXT



### DESCRIPTION

Our 32A extension lead offers simple and reliable 3-phase power connection for use in zone 1 and 2 hazardous areas. Constructed from IECEx certified industrial connectors and durable shielded cable, the leads are ideal for use in harsh environments.

### KEY FEATURES

- ATEX and IECEx certified for zone 1 and 2
- Simple plug-in operation
- Waterproof & dustproof
- AS/NZS 60079 compliant
- Available in various lengths

### TECHNICAL SPECIFICATION

Zone Rating

Temperature Classification

Voltage

Rated Current

Frequency

Ingress Protection

Pin-Out

Plug Options

Socket Options

Cable

Zone 1 & 2

T6

380-480V

32A

50/60Hz

IP66

3P+N+E / 3P+E

CEAG, STAHL \*

CEAG, STAHL \*

15m or 30m shielded LSZH \*\*

\* Other plug and socket options available upon request

\*\* Other cable lengths and types available upon request

## IECEX 63A EXTENSION LEAD

ORDER CODE: 63EXT

### DESCRIPTION

Our 63A extension leads offer simple and reliable 3-phase power connection for use in zone 1 and 2 hazardous areas. Constructed from IECEx certified industrial connectors and durable shielded cable, the leads are ideal for use in harsh environments.

This 63A extension lead is built around a robust integrated lifting frame with durable castors for maximum mobility.

As with all our power distribution products, our gas group IIC 3 phase extension leads are suitable for use in hydrogen gas group environments.

A perfect pairing with our IECEx certified 3 phase power distribution boards, our 3-phase extension leads are a safe and reliable way to bring power to your people.

### KEY FEATURES

- ATEX and IECEx certified for zone 1 and 2
- Simple plug-in operation
- Portable design with castors
- Robust frame
- Waterproof & dustproof
- AS/NZS 60079 compliant
- Available in various lengths



### TECHNICAL SPECIFICATION

Zone Rating	Zone 1 & 2
Temperature Classification	T6
Voltage	380-480V
Rated Current	63A
Frequency	50/60Hz
Pin Arrangement	3P+N+E / 3P+E
Ingress Protection	IP66
Plug Options	CEAG, STAHL *
Socket Options	CEAG, STAHL *
Cable	30m, 50m or 70m shielded LSZH **

\* Other plug and socket options available upon request

\*\* Other cable lengths and types available upon request